

SCG INFO TECH

E' il momento del grigio, nuovo protagonista della collezione Superclassica. Sette finiture ed otto formati che reinterpretano la pietra e ne esaltano la superficie. Naturale, lucida, bocciardata, incisa, antica e strutturata, Superclassica si veste in un modo sempre nuovo. La collezione include infine Patchy, agglomerato 60x120 e Riviera, porcellatano lucido da pavimento e rivestimento, che dona un sapore marinaro alla collezione. Superclassica offre così un'ampia scelta progettuale, ideale per ambienti residenziali e commerciali, interni ed esterni. My grey made your day!

It's time for GREY, the new star of the Superclassica collection. Seven finishes and eight sizes that redefine stone and enhance its surface. Natural, polished, bush-hammered, etched, antiqued and textured, Superclassica is dressed in an ever-changing way. Finally, the collection includes Patchy, a 60x120 cluster, and Riviera, a polished porcelain floor and wall tile that gives the collection a nautical flavor. Superclassica thus offers a wide range of design choices, ideal for residential and commercial, indoor and outdoor environments. My grey made your day!

TECHNICAL DETAILS

SUPERCLASSICA SCG

TECHNOLOGY PORCELLANATO DIGITALE HD AD IMPASTO COLORATO - HD DIGITAL COLORED BODY PORCELAIN

FINISH RETTIFICATO - RECTIFIED
NATURAL / FLAMED / HAMMERED / CRACK / GROOVED / CHEVRON / POLISHED / PATCHY

THICKNESS 9 MM

RIVIERA

TECHNOLOGY PORCELLANATO SMALTATO - GLAZED PORCELAIN

FINISH LUCIDO - LUX

THICKNESS 8,5 MM


LOBSTER WHITE BEIGE AZURE PINETA



SCG SURFACES




SCG SIZES



80X80 32”X32”
GRAPHIC NR. 8 CRACK




30X60 12”X24”
GRAPHIC NR. 40 NATURAL




60X120 24”X48”
GRAPHIC NR. 15 NATURAL
GRAPHIC NR. 15 POLISHED
GRAPHIC NR. 4 FLAMED
GRAPHIC NR. 30 CRACK
GRAPHIC NR. 6 GROOVED
GRAPHIC NR. 11 HAMMERED
GRAPHIC NR. 5 PATCHY



7,5X120 3”X48”
GRAPHIC NR. 120 NATURAL




MOSAIC 2,3X5,8
NET 30X30 12”X12”




60X60 24”X24”
GRAPHIC NR. 30 CRACK



7,5X60 3”X24”
GRAPHIC NR.>250 MIX



DX



SX

CHEVRON 20X80 8”X32”
GRAPHIC NR. 16

IN OGNI SCATOLA CI SONO 3 PEZZI DESTRI E 3 PZ SINISTRI.
IN EVERY BOX THERE ARE 3 RIGHT PIECES AND 3 LEFT PIECES.

SCG GROUTS

SCG

SCG Mapei 111 Silver Grey
R. LOBSTER Mapei 145 Terra di S.

colori stucchi consigliati / advised grouts colors

R. WHITE Kerakoll KK 2
R. BEIGE Mapei 130 Jasmine
R. AZURE Kerakoll KK 6
R. PINETA Mapei 119 London Grey

SCG SIZES AND TEXTURES

NATURAL



60X120
30X60
7,5X120

POLISHED



60X120

FLAMED



60X120

CRACK



80X80
60X120
60X60

GROOVED



60X120

HAMMERED




60X120

CHEVRON



20X80

PATCHY



60X120

*MIX



7,5X60
MOSAIC 30X30

*HAMMERED/GROOVED
NATURAL/FLAMED

SCG CODES

SIZE	Natural	Polished	Flamed	Crack	Grooved	Hammered	Chevron	Patchy	Mix
60X120 24”X48”	4101136	4101145	4101139	4101142	4101141	4101140	-	4101146	
60X60 24”X24”	-	-	-	4101144	-	-	-	-	
30X60 12”X24”	4101137	-	-	-	-	-	-	-	
80X80 32”X32”	-	-	-	4101143	-	-	-	-	
20X80 8”X32”	-	-	-	-	-	-	4101149	-	
7,5X120 3”X48”	4101147	-	-	-	-	-	-	-	
7,5X60 3”X24”	-	-	-	-	-	-	-	-	4101148
MOSAIC	-	-	-	-	-	-	-	-	4101150

	Lobster	White	Beige	Azure	Pineta
Riviera	4101095	4101093	4101098	4101096	4101099

SCG TECHNICAL FEATURES



IMPERVIOUS
TILE P1

NORMA STANDARD	CARATTERISTICHE FEATURES	VALORE PRESCRITTO REQUIRED VALUE	SUPERCLASSICA SCG
ISO 10545/2	DIMENSIONI - SIZE		
	lunghezza e larghezza length and width	± 0,6 % / ± 2 mm	± 0,6 % / ± 2 mm
	spessore thickness	± 5 % ± 0,5 mm	± 5 % ± 0,5 mm
	rettilineità degli spigoli straightness of sides	± 0,5 % ± 1,5 mm	± 0,5 % ± 1,5 mm
	ortogonalità wedging	± 0,5 % ± 2 mm	± 0,5 % ± 2 mm
	planarità flatness	± 0,5 % ± 2 mm	± 0,5 % ± 2 mm
ISO 10545/3	assorbimento d'acqua water absorption	≤ 0,5 %	0,3 %
ASTM C373	water absorption	≤ 0,5 %	meets the standards
ISO 10545/9	resistenza agli sbalzi termici thermal shock	nessuna alterazione visibile no visible alteration	resiste resistant
ASTM C484	thermal shock	unaffected	unaffected
ISO 10545/12	resistenza al gelo frost/freeze resistance	nessuna alterazione visibile no visible alteration	resiste resistant
ASTM C1026	frost/freeze resistance	unaffected	unaffected
ISO 10545/13	resistenza agli attacchi chimici chemical resistance	nessuna alterazione visibile no visible alteration	LA ≥ HB
ASTM C650	chemical resistance		A
ISO 10545/4	resistenza alla flessione breaking strength	≥ 35 N/ mm²	48 N/ mm²
ISO 10545/7	resistenza all'abrasione visible abrasion resistance		PEI IV
ASTM C1027	visible abrasion resistance	CLASS I-V	C.IV
ISO 10545/14	resistenza alle macchie stain resistance	≥ CLASSE 3	4
ASTM C1378	stain resistance	≥ CLASSE 3	4
ANSI A137.1	aesthetic classes	V0-V4	V1

RIVIERA TECHNICAL FEATURES



IMPERVIOUS
TILE P1

NORMA STANDARD	CARATTERISTICHE FEATURES	VALORE PRESCRITTO REQUIRED VALUE	RIVIERA
ISO 10545/2	DIMENSIONI - SIZE		
	lunghezza e larghezza length and width	± 0,9 mm	± 0,9 mm
	spessore thickness	± 0,5 mm	± 0,5 mm
	rettilineità dei lati straightness of sides	± 0,75 mm	± 0,75 mm
	ortogonalità wedging	± 0,75 mm	± 0,75 mm
	planarità flatness	± 0,75 mm	± 0,75 mm
ISO 10545/3	assorbimento d'acqua water absorption	≤ 0,5 %	0,3 %
ASTM C373	water absorption	≤ 0,5 %	meets the standards
ISO 10545/9	resistenza agli sbalzi termici thermal shock	nessuna alterazione visibile no visible alteration	resiste resistant
ASTM C484	thermal shock	unaffected	unaffected
ISO 10545/12	resistenza al gelo frost/freeze resistance	nessuna alterazione visibile no visible alteration	resiste resistant
ASTM C1026	frost/freeze resistance	unaffected	unaffected
ISO 10545/13	resistenza agli attacchi chimici chemical resistance	nessuna alterazione visibile no visible alteration	resiste resistant
ASTM C650	chemical resistance		unaffected
ISO 10545/4	modulo di rottura moduls of ropture	≥ 35 N/ mm²	46 N/ mm²
ISO 10545/14	resistenza alle macchie stain resistance	≥ CLASSE 3	5
ASTM C1378	stain resistance	≥ CLASSE 3	5
ANSI A137.1	aesthetic classes	V0-V4	V1

SCG PACKING

SCG	pcs	m²	kg/box	box/pal	m²/pal	kg/pal	thickness
80x80 ^{32"x32"}	2	1,28	24,83	40	51,20	993,20	9 mm
60x120 ^{24"x48"}	2	1,44	27,94	30	43,20	838,20	9 mm
60x60 ^{24"x24"}	3	1,08	20,95	40	43,20	838,00	9 mm
30x60 ^{12"x24"}	6	1,08	20,95	40	43,20	838,00	9 mm
7,5x120 ^{3"x48"}	8	0,72	14,50	50	36,00	725,00	9 mm
7,5x60 ^{3"x24"}	12	0,54	10,70	48	25,92	513,60	9 mm
Chevron	6	0,96	18,60	48	46,08	892,80	9 mm
Mosaic	11	-	19,20	-	-	-	9 mm
Riviera	78	0,585	10,65	125	73,13	1331,25	8,5 mm

SUPERCLASSICA SCG	DIN EN 16165 scivolosità anti-slip	DCOF dynamic coefficient of friction
NATURAL	R10	≥ 0,42
POLISHED	-	-
FLAMED	R10 A+B	≥ 0,42
CRACK	R10	≥ 0,42
GROOVED	R10	≥ 0,42
HAMMERED	R11 A+B	≥ 0,42
PATCHY	R10	≥ 0,42
CHEVRON	R10	≥ 0,42